

Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
12 mm - Embeddable, Extended Length eurofast® Connection 	Bi 2U-M12E-AD4X-H1144	M4405060	Uprox	2	2-Wire DC
	Bi 3-M12E-AD4X-H1141	T4405080	Ext. Range	3	
	Bi 2-M12E-AN6X-H1141	T4606602		2	3-Wire DC NPN
	Bi 3U-EM12E-AN6X-H1141	M1634351	Uprox	3	
	Bi 3U-EM12HE-AN6X2-H1141	M1634311	Stoneface, Uprox	3	
	Bi 3U-EM12HE-AN6X2-H1141/S1589	M1634397	weldguard	3	
	Bi 3U-M12E-AN6X-H1141	M1634151	Uprox	3	
	Bi 4-M12E-AN6X-H1141	T4607193	Ext. Range	4	
	Bi 4-EM12HE-AN6X-H1141/S1589	T4607185	Ext. Range, weldguard	4	
	Bi 3U-EM12E-AP6X-H1141	M1634343	Uprox	3	3-Wire DC PNP
	Bi 3U-M12E-AP6X-H1141	M1634148	Uprox	3	
	Bi 3U-EM12HE-AP6X2-H1141	M1634310	Stoneface, Uprox	3	
	Bi 3U-EM12HE-AP6X2-H1141/S1589	M1634398	Uprox, weldguard	3	
	Bi 4-M12E-AP6X-H1141	T4608030	Ext. Range	4	
	Bi 4-EM12HE-AP6X-H1141/S1589	T4607184	Ext. Range, weldguard	4	
	Bi 3U-M12E-VN4X-H1141	M1580354	Uprox	3	4-Wire DC NPN
	Bi 4-M12E-VN6X-H1141	T1643201	Ext. Range	4	
	Bi 3U-M12E-VP4X-H1141	M1580252	Uprox	3	4-Wire DC PNP
	Bi 4-M12E-VP6X-H1141	T4608092	Ext. Range	4	
	Bi 2-M12E-Y0X-H1141	T4606490			2

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.