

Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing	Output
12 mm - Embeddable, picofast® Connection 	Bi 4U-M12-AP6X-V1131	M1634780		4	3-Wire DC PNP
12 mm - Embeddable, eurofast® Connection 	Bi 4-M12K-AN6X-H1141	T4607101	Short Barrel	4	3-Wire DC NPN
12 mm - Embeddable, eurofast Connection 	Bi 2-M12-AD4X-H1141	T4406500		2	2-Wire DC
	Bi 3-M12-AD4X-H1141	T4405041	Ext. Range	3	
	Bi 2-EM12-AN6X-H1141	T4606601		2	3-Wire DC NPN
	Bi 2-M12-AN6X-H1141	T4606600		2	
	Bi 3U-EM12-AN6X-H1141	M1634350	Uprox	3	
	Bi 3U-M12-AN6X-H1141	M1634150	Uprox	3	
	Bi 3U-M12-AN6X2-H1141	M1634155	Uprox	3	
	Bi 4-M12-AN6X-H1141	T4607100	Extended Range	4	
	Bi 4U-EM12-AN6X-H1141	M1634827		4	
	Bi 4U-M12-AN6X-H1141	M1634824		4	
	Bi 2-EM12-AP6X-H1141	T4606501		2	3-Wire DC PNP
	Bi 2-M12-AP6X-H1141	T4606500		2	
	Bi 3U-EM12-AP6X-H1141	M1634340	Uprox	3	
	Bi 3U-EM12H-AP6X-H1141	M1634312	Uprox, Stoneface	3	
	Bi 3U-M12-AP6X-H1141	M1634140	Uprox	3	
	Bi 3U-M12-AP6X2-H1141	M1634145	Uprox	3	
	Bi 4-M12-AP6X-H1141	T4607000	Extended Range	4	
	Bi 4U-EM12-AP6X-H1141	M1634807		4	
	Bi 4U-EM12-AP6X-H1141/S1589	M1634897-1	weldguard	4	
	Bi 4U-M12-AP6X-H1141	M1634804		4	
Bi 2-M12-VN6X-H1141	T1643000	Comp. Outputs	2	4-Wire DC NPN	
Bi 4-M12-VN6X-H1141	T1643200	Ext. Range, Comp.Outputs	4		
Bi 2-M12-VP6X-H1141	T1633000	Comp. Outputs	2	4-Wire DC PNP	
Bi 4-M12-VP6X-H1141	T1633200	Ext. Range, Comp.Outputs	4		
Bi 4-EM12-VP6X-H1141	T1633201	Ext. Range, Comp.Outputs	4		
Bi 2-M12-Y1X-H1141	M4010200		2	2-Wire DC Namur	

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.