

4 and 5-Wire Receptacles, Rear Mount with Leads

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A (4 & 5 pole)
- 60 VAC/75 VDC, 2A (6 pole)



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FKFD ..</p> <p>Typical panel cutout is 15.3 x 14 mm.</p>	FKFD 4.4-*	FSFD 4.4-*	4x22 AWG, 105°C, mates with 4-pin cordsets	<p>Female</p>
	FKFD 4.4-*/S621	FSFD 4.4-*/S621	4x18 AWG, 105°C, mates with 4-pin cordsets	<p>Male</p>
<p>FSFD ..*</p> <p>Typical panel cutout is 15.3 x 14 mm.</p>	FKFD 4.5-*	FSFD 4.5-*	5x22 AWG, 105°C, mates with 5-pin cordsets	<p>Female</p>
	FKFD 4.5-2/S653	FSFD 4.5-2/S653	4x22 AWG, Drain, 105°C, 5.1 mm OD, mates with 5-pin cordsets, 4 Conductors PVC Foil Shielded with Drain Wire to pin 5	<p>Male</p>
	FKFD 6-*	FSFD 6-*	UL, CSA, 6x24 AWG, 105°C, mates with 6-pin cordsets	<p>Female</p>
				<p>Male</p>

* Length in meters. Standard lead length is 0.5 meters. Consult factory for other lengths. Standard housing material is nickel plated brass "FSFD.."; "FSFDV.." indicates stainless steel. To specify PVC jacketed cable, add "/S717" to the end of the part number.